

BETONAMIT® | Das Original

Materialverbrauch

Berechnung nach Bohrlochdurchmesser

Dichte BETONAMIT® [kg/dm³]

1.75



Bohrlochdurchmesser [mm]	Bohrlochvolumen [dm ³ /m]	BETONAMIT® [kg/m]
20	0.31	0.55
25	0.49	0.86
28	0.62	1.08
30	0.71	1.24
32	0.80	1.41
35	0.96	1.68
38	1.13	1.98
40	1.26	2.20
41	1.32	2.31
43	1.45	2.54
45	1.59	2.78
48	1.81	3.17
51	2.04	3.57

Bohrlöcher pro Quadratmeter

Bohrraster [m]	Bohrlöcher bei 1 m ²	Bohrlöcher pro m ²
0.20	16.00	16.00
0.25	9.00	9.00
0.30	5.44	5.44
0.35	3.45	3.45
0.40	2.25	2.25
0.45	1.49	1.49
0.50	1.00	1.00

Bohrraster [m]	Bohrlöcher bei 4 m ²	Bohrlöcher pro m ²
0.20	81.00	20.25
0.25	49.00	12.25
0.30	32.11	8.03
0.35	22.22	5.56
0.40	16.00	4.00
0.45	11.86	2.97
0.50	9.00	2.25

Bohrraster [m]	Bohrlöcher bei 100 m ²	Bohrlöcher pro m ²
0.20	2'401.00	24.01
0.25	1'521.00	15.21
0.30	1'045.44	10.45
0.35	760.18	7.60
0.40	576.00	5.76
0.45	450.38	4.50
0.50	361.00	3.61

Bohrraster [m]	Bohrlöcher bei 400 m2	Bohrlöcher pro m2
0.20	9801.0000	24.5025
0.25	6241.0000	15.6025
0.30	4312.1111	10.7803
0.35	3152.0204	7.8801
0.40	2401.0000	6.0025
0.45	1887.4198	4.7185
0.50	1521.0000	3.8025

Bohrraster [m]	Bohrlöcher bei 900 m2	Bohrlöcher pro m2
0.20	22'201.00	24.67
0.25	14'161.00	15.73
0.30	9'801.00	10.89
0.35	7'176.51	7.97
0.40	5'476.00	6.08
0.45	4'312.11	4.79
0.50	3'481.00	3.87

Bohrraster [m]	Bohrlöcher bei 1600 m2	Bohrlöcher pro m2
0.20	39'601.00	24.75
0.25	25'281.00	15.80
0.30	17'512.11	10.95
0.35	12'833.65	8.02
0.40	9'801.00	6.13
0.45	7'724.46	4.83
0.50	6'241.00	3.90

Bohrraster [m]	Bohrlöcher bei 10'000 m2	Bohrlöcher pro m2
0.20	249'001.00	24.90
0.25	159'201.00	15.92
0.30	110'445.44	11.04
0.35	81'062.22	8.11
0.40	62'001.00	6.20
0.45	48'939.27	4.89
0.50	39'601.00	3.96

Bohrraster [m]	Bohrlöcher bei 1'000'000 m2	Bohrlöcher pro m2
0.20	24'990'001.00	24.99
0.25	15'992'001.00	15.99
0.30	11'104'445.44	11.10
0.35	8'157'552.02	8.16
0.40	6'245'001.00	6.25
0.45	4'933'828.16	4.93
0.50	3'996'001.00	4.00